



DESIGN <i>[Signature]</i>	DRAWN BY <i>[Signature]</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED <i>[Signature]</i>	APPROVED <i>[Signature]</i>	DRAWING NO. M1010-S	REV. A SHEET 1 OF 1
DATE 01.06.13		TITLE 1010-1025 SHEET SCALE NTS	
A	01.06.13	NEW ISSUE	
A1	04.03.09 <i>[Signature]</i>	ADD ASTM A1008 AND COLD ROLLED	

PURCHASE MATERIAL:

ASTI 1010-1025 OR ASTM A36 /A366/A1008  
OR CSA G40-21, 38W/44W/50W/60W/70W

MINIMUM YIELD TENSILE STRENGTH = 28 KSI

MINIMUM ULTIMATE TENSILE STRENGTH = 42 KSI

COLD ROLLED

PART NUMBER:

M1010-S | TT | GA WHERE TT = GAUGE THICKNESS  
GA

EG. 16 GAUGE STEEL = M1010-S16GA

RELEASED  
01.06.15 *[Signature]*

Copyright © 2001 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.